



HT632系列 变频输出专用滤波器

- 变频器输出端专用
- 与输入HT5310系列配套使用，效果更佳



型 号	额定 电流 A	连接方式		外壳
		 焊片	 螺栓	
HT632-6-L8-C31	6	L8	--	C31
HT632-6-M4-C31	6	--	M4	C31
HT632-10-L8-C31	10	L8	--	C31
HT632-10-M4-C31	10	--	M4	C31
HT632-16-L8-C31	16	L8	--	C31
HT632-16-M4-C31	16	--	M4	C31
HT632-20-L8-C31	20	L8	--	C31
HT632-20-M4-C31	20	--	M4	C31
HT632-25-M4-C31	25	--	M4	C31
HT632-32-M6-E32	32	--	M6	E32
HT632-42-M6-E32	42	--	M6	E32
HT632-50-M6-E32	50	--	M6	E32
HT632-65-M6-G32	65	--	M6	G32
HT632-80-M8-G33	80	--	M8	G33
HT632-100-M8-G33	100	--	M8	G33
HT632-120-M8-G33	120	--	M8	G33
HT632-150-M10-G35	150	--	M10	G35
HT632-180-M10-G35	180	--	M10	G35

* 连接方式：L8-焊片（6.3*0.8）；M4-M4螺栓；M6-M6螺栓；M8-M8螺栓；M10-M10螺栓。

工作频率：0~400Hz

额定电压：440VAC

额定电流：6~180A（50℃时），最大值

耐压测试(2秒钟)：2250VDC(L-L) 2700VDC(L-E)

温度范围：-25℃~+85℃



HUGETON

惠博顿

HT632系列 变频输出专用滤波器

外形尺寸

单位：mm 公差：±1

